

# Q8 Formula Ultra 0W-20

## Description

Synthetic SAE 0W-20 passenger car engine oil with demonstrated fuel saving characteristics

## Application

Specially formulated for passenger car gasoline engines requiring a fuel saving low viscosity engine oil.

Q8 Formula Ultra may be used as engine lubricant when one or more of the following specifications are used to describe the required lubricant quality:

## Specifications

API SN/ILSAC GF-5

## Benefits

- Specially developed for reducing fuel consumption
- Up to 2% Fuel Economy Improvement
- Extended drain interval capability
- Excellent engine protection after cold starting
- Demonstrated fuel consumption reduction in gasoline engines
- Excellent engine performance at all driving conditions
- Outstanding protection against foam formation, rust and corrosion

Properties	Method	Unit	Typical
Viscosity Grade			SAE 0W-20
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	840
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	8.6
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	47
Viscosity Index	D 2270	-	163
Apparent Viscosity, -35 °C	D 5293	mPa.s	5600
Pour Point	D 97	°C	-42
Flash Point	D 92	°C	204
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>2.6

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

